


2.54mm Flat Flex Jumper Cable

Male to Male Long Solder Tab












PRODUCT DETAILS

The Flex Connection range of Flat Flex Jumper Cables are manufactured with Flexible Flat Cables (FFCs) produced by laminating bare copper conductors between 2 layers of tough, flexible flame retardant UL VW-1 rated polyester insulators. We terminate either end of the Jumper Cable with connectors from leading manufacturers such as Memcon, Tyco, Nicomatic and others. Flex Connection Jumpers provide high reliability and retention compared to traditional FFCs used with ZIF/LIF products with low contact resistance and high current options while maintaining a high level of flexibility.


FEATURES

-  Highly Flexible
-  Light Weight
-  Extremely Thin
-  Quality Design
-  Suitable to Fold


APPLICATIONS

- | | |
|---|---|
|  Domestic Appliance |  IT Equipment |
|  Consumer Electronics |  Office Equipment |
|  Automotive Industry |  Robotics |
|  Medical Applications |  Industrial |
|  Telecommunications | |

MATING PCB




DIMENSION OUTLINE



ELECTRICAL AND MECHANICAL PROPERTIES

Flat Cable Material	Flat Copper Conductors laminated between 2 layers of White Polyester Insulation
Contact Style	MLST241T Long Male Solder Tab
Contact Material	0.20mm thick Phosphor Bronze
Pitch	2.54mm
Number of Conductors	2 to 26 ways as standard
Conductor Size	1.57mm (width) x 0.076mm thick bare copper
Current Rating	3A AC / Conductor
Operating Voltage	300V RMS
Dielectric Strength	Over 1000 M Ω /M @2000VDC (20 deg C)
Resistance	<0.2 Ω /M


OTHER OPTIONS




FOLDING




BENDING



SHIELDING



LABELING



SLEEVING

PART NUMBERING BREAKDOWN

